precise PH&Conductivity meter

DiaSys reference: **950185**

Detailed description

- Handheld
- High-performance CPU chip
- High accuracy with high-precision AD converter
- EC, PH and Temperature display
- Simple operation
- Waterproof housing
- Conductivity range from 0.1 to µS/cm to 199 µcm/cm.
- Automatic Temperature Compensation

SPECIFICATIONS:

- Measuring range : 0.0☐14.0pH ; 0~199.9uS/cm
- Accuracy : ±0.1pH ; ±2%FS
- Resolution : 0.1pH ; 0.1uS/cm
- Automatic Temperature Compensation : 0℃☐50℃
- Operating Temperature : 0℃☐50℃

- PH calibration : 3 points automatic calibration (4.01; 6.86;9.18)
- Conductivity calibration : correction1 point automatic calibration 84uS/cm
- Automatic shutdown : 10 minute auto shut off
- Backlight : high brightness backlight design
- Low voltage indication : YES
- Automatic conversion of C / F : YES
- Hold Function : YES
- Low voltage indication : YES
- Display : Dual display of measure (EC or pH) and temperature
- Battery : 6V (4 * AG13 button batteries)
- Dimensions : 188mm×38mm
- Weight : 82g

CT6321 PH&EC meter user manual

From:
https://diasys-technologies.com/waterpurifiers/ - **DiaSys Water Purifier Systems**

Permanent link:
https://diasys-technologies.com/waterpurifiers/doku.php?id=ct6321&rev=1553527076

Last update: **2019/03/25 15:17**