2025/09/14 18:51

OSMOSERS-TROUBLESHOOTING

PROBLEMS POSSIBLES CAUSES SUGGESTED ACTION

- indicator *PUMP* switched off| - Switch on OFF position.| Switch ON the device|

	 The water supply of the tap closed or insufficient pressure (in that case the light "SOURCE" is on). 	Check the water supply
	- water hose folded or obstructed	Check that the inlet pipe is not damaged.
- No production of purified water - Power light ON - all control light indicators OFF	- on power supply	Check and replace the fuses
Not or low purified water	Pre-treatment clogged	Replace the pre-treatment filters before the RO membrane
- Not or low purified water production - indicator <i>PUMP</i> light ON - Pump running	Low flow of inlet water	Increase the flow of the inlet water
light ON Tump running	Reverse osmosis membrane clogged	Change the membrane
- Not or low purified water production - indicator <i>PUMP</i> light ON - Pump always OFF		Replace the pump fuse
Light indicators FULL and PUMP alternate	Defectiveness of the high-pressure sensor or check valve.	Pressure sensor and check valve
	- Watertank hand valve closed.	Turn ON the watertank hand valve
Lack of pressure and low flow output	 volume of pure water need above the specification of the water purifier 	Wait the watertank is filled again
	 Lack of pressure in the pressurised watertank 	Re-adjust the air-pressure of the water tank
purified water conductivity too high	Resin saturated.	Replace resin cartridge or bottle
- POWER & FULL indicators ON - Pump OFF - Drain flowing continuously	- Inlet solenoid valve defective	Replace the inlet solenoid valve
Conductivity meter display OFF	Batteries out of order	Replace the batteries

From:

https://diasys-technologies.com/waterpurifiers/ - DiaSys Water Purifier Systems

Permanent link:

https://diasys-technologies.com/waterpurifiers/doku.php?id=rotroubleshooting&rev=1554382855

Last update: 2019/04/04 13:00